

FlickTLIME



Large

5kW

80.4%



Medium

5kW Output

85.1%



Small

4.9kW 82.7%



UK UK CE OPTIONAL Sende Control Options Control Options (Sal declaring Window)





















SMALL 139-S-FLICKRFL

Wood

4.9

Fuel

kW



MEDIUM 139-M-FLICKRFL

Wood

Fuel



LARGE 139-L-FLICKRFL

Wood

Fuel



Efficiency	82.7%	
Flue size	125mm	
Outlet	Top & rear	
Outside air	Optional	
Materials	Steel body, cast iron door	
Weight	65kg	
I I a l'arla A	(0/	

Outside all	Optional	
Materials	Steel body cast iron door	
Weight	65kg	
Height	494mm	
Width	446mm	
Depth	332mm	

Depth	332mm	
Distance to combustibles		
Back	300mm	
Sides	400mm	
Distance to non-combustibles		
Back	50mm	
Sides	75mm	
Hearth projection		
Front	400mm	
Side	150mm	
Distance to furniture		
Front	1075mm	

Suitable for 12mm hearth Yes

r. v v	5		
Efficiency	85.1%		
Flue size	125mm		
Outlet	Top & rear		
Outside air	Optional		
Materials	Steel body, cast iron door		
Weight	64kg		
Height	530mm		
Width	410mm		
Depth	332mm		
Distance to combustibles			
Back	250mm		
Sides	400mm		
Distance to nor	n-combustibles		
Back	50mm		
Sides	75mm		
Hearth projection			
Front	400mm		
Side	150mm		
Distance to furniture			
Front	1075mm		
Suitable for 12mm hearth			
Yes			

ruei	vvoou	
kW	5	
Efficiency	80.4%	
Flue size	125mm	
Outlet	Top & rear	
Outside air	Optional	
Materials	Steel body, cast iron door	
Weight	76kg	
Height	590mm	
Width	490mm	
Depth	332mm	
Distance to combustibles		
Back	250mm	
Sides	400mm	
Distance to non-combustibles		
Back	50mm	
Sides	75mm	
Hearth projection		
Front	400mm	
Side	150mm	
Distance to furniture		
Front	1075mm	
Suitable for 12mm hearth		



